
COLT TRAILER HOISTS



1-800-533-0494 • www.colthoists.com

COLT TRAILER HOISTS



Fully Greaseable – Pivot Points

COLT HOIST CAPACITY for 45° Dump Angle (in tons) Hoist Model and Overhang Body TB10DP **TB-8** TB-10 **TB-12 TB-14 TB-16 TB-18 TB-20** Length 12" 18" 18" 18" 24" 24" 24" 18" 8.6 4.5 7.4 3.8 8 6.5 3.2 6.8 10.9 16.7 5.2 5.3 8.5 12.5 14' 4.3 10 12.8 6.9 16' 8.3 11.7 14.3 18' 10.8 12.3 13.2 20' 11.7 22' 10.4 24' 9.4

Capacity based on water-level load.

Caution: The combined weights of trailer frame and body, hoist and load must not exceed the gross weight rating of any component.

COLT HOIST SPECIFICATIONS (for 45° Dump Angle)								
	TB10DP	TB-8	TB-10	TB-12	TB-14	TB-16	TB-18	TB-20
Class		Α	В	С	D	E	Е	F
Hoist Type	Direct Push	Scissors						
Mounting Height (in.)	5	5.25	6.5	7	7	7.75	8	8
Minimum Vertical Height* (in.)	n/a	5	8	8	8.5	9	11	11
"M" Dimension** (in.)	n/a	51.5	79	77.25	96.75	90.25	100	128
Maximum Hydraulic Flow Rate (GPM)	3	3	4	6	6	9	9	9
Maximum "Up" Pressure (PSI)	3200	3200						
Maximum "Down" Pressure (PSI)	1500	1500				1000		
Cylinder Bore & Stroke (in.)	3.75 x 28	3.5 x 10	4 x 16	5 x 16	5 x 21	6 x 19	6 x 23	6 x 29
Chromed Cyl. Shaft Diameter (in.)	1.15	1.5	2	2	2.25	2.5	2.5	2.75
Approx Weight (lbs)	131	205	305	340	415	670	750	855

^{*} Minimum Vertical Height is the distance between rear hinge pivot to floor

**"M" Dimension is the distance between the rear hinge pivot and the lower crosstube of the hoist in a standard mounting position



Trailer Hoists 1-800-533-0494 • www.colthoists.com

