



For more info...

Call: 484-241-6910

Email: forestry@versalifteast.com



CARRIER

- KERSHAW MODEL ATC7
- Caterpillar Engine
- 127 HP@2200 RPM
- Engine enclosed by Heavy Duty Engine Cowling with (4) Composite Side Doors
- Caterpillar Fixed Position, Open Drive, operator controlled selectable lockout transmission
- Speed Power Shift
- Four Wheel wet disc service brakes, peddle operated from cab
- Failsafe hydraulic operated drive line parking brake
- 12VDC 85 amp Electrical System
- (2) 1050 CCA Batteries
- Cab Fan
- Travel Lights
- Backup Alarm

KERSHAW VO260 SKIDDER

CONFIGURATION

- Liquid Cooled 4.4 Liter CAT Engine
- Rear Mounted 20,000 LB Winch
- Hydraulic Push Blade
- Front and Rear Frames connected by articulating joints that allow 15° Vertical and 45° Horizontal Articulation
- Platform Access Steps and Decking
- Angled Roof with ¼" Lexan Viewing Window
- Suspension Seat
- Power View Engine Monitor
- Tilt Steering

LIFT

- Versalift® VO260, per ANSI 92.2
- Working height: 65-feet
- 24" x 24" Platform, 350 LB cap, with cover
- Individual Lever Controls
- Full Pressure Open Center Hydraulic System
- Continuous Unrestricted Rotation
- Full Length Sub Frame
- Hydraulic Tool Outlets at Platform
- (2) Sets of A-Frame Outriggers
- (2) Sets of Lifton Outrigger Pads with Holders
- Teflon Bearings at all Boom Pivot Points
- No Mandatory Rebuild Required
- Emergency Power System
- Outrigger Boom Interlock

SAFETY

- Stability Test, Load Test & Dielectric Test
- 5 LB ABC Fire Extinguisher & Bracket
- Triangle Reflector Kit & First Aid Kit
- DOT Inspection
- Safety Belt & Lanyard
- Non-Skid Paint, as required
- Unit Will Have Current ANSI & Dielectric Inspection
- Versalift East QC Inspection Program



VERSALIFT® FORESTRY PRODUCTS www.versalifteast.com