

05*L*-*H* 

PowerTraxx 05L-H, a multi-purpose unit can be utilized as flatbed carrier, personnel carrier, or small to medium sized digger-derricks, aerial devices, and other attachments. The 05L-H 10,000 lbs. payload capacity utilizes 33" wide D-dent tracks to evenly distribute the load for an incredibly low ground pressure rating. Its 160 hp Cummins® diesel engine helps to make this light unit quick and manoeuvrable in extreme operating conditions.

**Main Dimensions** 



Main Dimensions			
Overall Length	192"	Steering	
Overall Width	99"	Type	Electronic Joystick
Overall Height	102"	Type	Electronic Joystick
Ground Clearance	17"		
		Tracks	
Weights		Туре	Rubber With Steel Grousers
Basic Vehicle Weight	12,500 Lbs.	Belts	12" x 6 ply, Goodyear Rubber
Pauload Canacity	10,000 Lbs.	Bars	D-Dent, 33" x ½", Heavy Duty
Payload Capacity Gross Vehicle Weight	22,500 Lbs.		
Closs venicle weight	22,500 E0s.	Reinforcing Bar	Optional
Ground Pressure – Unloaded	1.47 psi	Electrics	
Ground Pressure -	2.64 psi	Alternator	160 Amp
Loaded		Batteries	2 x 200 Amp Hour, 1125 CCA
<b>F</b> :		Starter	4.8 kW, 12 V
<b>Engine</b> Type	Cummins QSB, Tier 3	Driving Lights	2 Forward, 2 Rear
Capacity	4.5 Litres	Other	Back-Up Alarm, Master Switch
Horse Power	160 @ 2100 RPM	ouloi	Buck Op Mulli, Muster Switch
Electrical System	12 V		
Fuel Tank Capacity	40 US Gal	Cabin	
Tuel Tulk Capacity	+0 05 Gui	Туре	Single Person, Enclosed, ROPS 45,000 Lbs.
Drive System		Heater	40,000 BTU With Adjustable Defrosters
Туре	Hydrostatic	Air Conditioning	Available
Location	Rear	Other	Sunroof/Escape Hatch, One (1) Seat With Seatbelt
Pump Drive	Funk, Triple Pad, Series 28000		Dome Light, Panel Lights
Hydrostatic Pumps	Sauer 90 Series, 90cc		
	Variable Displacement	Instruments	
Hydrostatic Motors	Sauer 51 Series, 160cc	Instruments	
	Two (2) Speed, Variable Displacement	Gauges	Hydrostatic Oil Temp., Voltmeter, Hourmeter, Engine
Planetaries	Fairfield W12D		Oil Pressure, Engine Temp., Fuel Level, Tachometer
Speed	10 mph		
Drive Sprocket	14 Tooth, Steel Hub Sprocket	Manuals	
-	Replaceable Urethane	Туре	2 Parts, 2 Maintenance
Idler Sprocket	12 Tooth, Steel Hub Sprocket		
	Replaceable Urethane	<b>Optional Equipment</b>	
<b>6</b>			
Suspension	Here D ( Assled Well's Descent	Cold Weather Package	Steel Flat Track
Туре	Heavy Duty Arched Walking Beams Solid Steel, Urethane Bushings	Front Winch	Rubber Covered Flat track
	Solid Steel, Oremane Bushings	Dual Lever Steering	Two Person Cab
Load Wheels	650 x 16, Solid Rubber Tire, 3 Piece Steel Rim	Piece Steel Rim Other Options Available Upon Request	
DoworTroxy Vohiolos Inc			

PowerTraxx Vehicles Inc. 150 Regional Rd. 10, Whitefish, ON, Canada P0M 3E0 ● T: 888-797-8799 F: 705-866-4433