

10S-H

PowerTraxx 10S-H hydrostatically driven track vehicle boasts a robust, heavily reinforced and extended frame, accompanied by a heavy duty suspension—giving it a 20,000 lbs. carrying capacity—making it the perfect application for digger-derricks, material handling aerial devices, and other various types of equipment. This vehicle rides on 33" wide D-dent tracks which give it an incredibly low ground pressure, and is powered by a Cummins® diesel engine compliant with today's emission regulations.

	TATCH	

Main Dimensions				
Overall Length	286"			
Overall Width	102"	Steering	Electronic I. edit	
Overall Height	112"	Туре	Electronic Joystick	
Ground Clearance	17"			
Weights		Tracks		
Basic Vehicle Weight	20,000 Lbs.	Туре	Rubber With Steel Grousers	
Dusie veniere wergin	20,000 E03.	Belts	12" x 6 ply, Goodyear Rubber	
Payload Capacity	20,000 Lbs.	Bars	D-Dent, 33" x <sup>1</sup> / <sub>2</sub> ", Heavy Duty	
Gross Vehicle Weight	40,000 Lbs.	Reinforcing Bar	Optional	
Ground Pressure –	1.96 psi	Reinforeing Bur	optional	
Unloaded		Electrics		
Ground Pressure –	3.90 psi	Alternator	160 Amp	
Loaded		Batteries	2 x 200 Amp Hour, 1125 CCA	
Engine		Starter	4.8 kW, 12 V	
Туре	Cummins QSB, Tier 3	Driving Lights	2 Forward, 2 Rear	
Capacity	6.7 Litres	Other	,	
Horse Power	215 @ 2100 RPM	Other	Back-Up Alarm, Master Switch	
Electrical System	U 12 V			
Fuel Tank Capacity	50 US Gal	Cabin		
		Туре	Single Person, Enclosed, ROPS 45,000 Lbs.	
Drive System		Heater	40,000 BTU With Adjustable Defrosters	
Туре	Hydrostatic	Air Conditioning	Available	
Location	Front or Rear	Other	Sunroof/Escape Hatch, One (1) Seat With Seatbelt	
Pump Drive	Funk, Triple Pad, Series 28000 Sauer 90 Series, 90cc		Dome Light, Panel Lights	
Hydrostatic Pumps	Variable Displacement			
Hydrostatic Motors	Sauer 51 Series, 160cc	Instruments		
119 41 00 4410 1,100010	Two (2) Speed, Variable Displacement	Gauges	Hydrostatic Oil Temp., Voltmeter, Hourmeter, Engine	
Planetaries	Fairfield W12D	Guuges	Oil Pressure, Engine Temp., Fuel Level, Tachometer	
Speed	8 mph			
Drive Sprocket	14 Tooth, Steel Hub Sprocket	Manuals		
	Replaceable Urethane	Туре	2 Parts, 2 Maintenance	
Idler Sprocket	12 Tooth, Steel Hub Sprocket	rype	2 Turts, 2 Waliteitailee	
	Replaceable Urethane			
а <b>і</b>		<b>Optional Equipment</b>		
Suspension		Cold Weather Package	Steel Flat Track	
Туре	Heavy Duty Arched Walking Beams Solid Steel, Urethane Bushings	Front Winch	Rubber Covered Flat track	
		Dual Lever Steering	Two Person Cabin	
Load Wheels	650 x 16, Solid Rubber Tire, 3 Piece Steel Rim	Oth	er Options Available Upon Request	
		Other Options Available Opon Request		

**PowerTraxx Vehicles Inc.** 150 Regional Rd. 10, Whitefish, ON, Canada POM 3E0 • T: 888-797-8799 F: 705-866-4433