15W-H

PowerTraxx 15W-H utilizes a strengthened and heavily reinforced frame that is widened for added stability. This vehicle comes standard as hydrostatically rear driven and rides along 40" wide D-dent tracks. The option of front drive is available, and creates more choices for devices such as elevator units that can be sunk into the frame to reduce traveling heights. Powering this unit is a Cummins® electronic diesel engine that provides an incredible 275 hp, powerful enough to move this unit through the most extreme terrain and conditions.

Main Dimensions

| Overall Length | 300" |
|------------------|------|
| Overall Width | 126" |
| Overall Height | 114" |
| Ground Clearance | 17" |

Weights

| Basic Vehicle Weight | 26,000 Lbs. |
|--|----------------------------|
| Payload Capacity Gross Vehicle Weight | 30,000 Lbs. 56,000 Lbs. |
| Ground Pressure – | 1.98 psi |

1.98 psi Unloaded

Ground Pressure -3.90 psi Loaded

Engine

Cummins QSC, Tier 3 Type Capacity 8.3 Litres Horse Power 275 @ 2100 RPM Electrical System 12 V Fuel Tank Capacity 60 US Gal

Drive System

Type Hydrostatic Front or Rear Location Pump Drive Funk, Triple Pad, Series 28000 Sauer 90 Series, 90cc Hydrostatic Pumps Variable Displacement Hydrostatic Motors Sauer 51 Series, 160cc Two (2) Speed, Variable Displacement

Planetaries Fairfield W12D Speed 8 mph 14 Tooth, Steel Hub Sprocket Drive Sprocket Replaceable Urethane Idler Sprocket 14 Tooth, Steel Hub Sprocket Replaceable Urethane

Suspension

Heavy Duty Arched Walking Beams Type Solid Steel, Urethane Bushings

Load Wheels 825 x 20, Solid Rubber Tire, 3 Piece Steel Rim



Steering

Type Electronic Joystick

Tracks

Type Rubber With Steel Grousers Belts 15" x 6 ply, Goodyear Rubber Bars D-Dent, 40" x 1/2", Heavy Duty Reinforcing Bar Optional

Electrics

Alternator 160 Amp **Batteries** 2 x 200 Amp Hour, 1125 CCA Starter 4.8 kW, 12 V **Driving Lights** 2 Forward, 2 Rear Other Back-Up Alarm, Master Switch

Cabin

Type Single Person, Enclosed, ROPS 60,000 Lbs. Heater 40,000 BTU With Adjustable Defrosters Air Conditioning Optional Other Sunroof/Escape Hatch, One (1) Seat With Seatbelt

Instruments

Gauges Hydrostatic Oil Temp., Voltmeter, Hourmeter, Engine Oil Pressure, Engine Temp., Fuel Level, Tachometer

Dome Light, Panel Lights

Manuals

Type 2 Parts, 2 Maintenance

Optional Equipment

Cold Weather Package Steel Flat Track Front Winch Rubber Covered Flat track **Dual Lever Steering** Digital Inclinometer

Other Options Available Upon Request