



35585 Curtis Boulevard • Eastlake, Ohio 44095 • (440) 951-8633 • (440) 951-4341 FAX

---

## **EnviroLogic® BioFlush**

### **Biodegradable , Non-toxic flush oil**

---

#### **Description**

EnviroLogic® BioFlush is a carefully designed fluid which helps to flush and remove petroleum oil from hydraulic systems. This is done when converting hydraulic systems to the use of environmentally safe, biodegradable fluids. EnviroLogic® BioFlush will condition the internal hydraulic system to help optimize both overall system performance and fluid biodegradability.

---

#### **Typical Properties**

Flash Point, °F	ASTM D-92	>400
Specific Gravity, 60°F	ASTM D-1122	
0.92		
Viscosity @ 40°C, cSt	ASTM D-445	46
Viscosity Index	ASTM D-2270	>200
Pour Point, °C	ASTM D-97	-36

---

#### **The proper use of EnviroLogic® BioFlush**

- 1. Run equipment until warm. Drain petroleum hydraulic fluid.**
- 2. Fill system with EnviroLogic® BioFlush. Run equipment for 5 minutes until fluid is completely circulated.**
- 3. Drain the BioFlush.**
- 4. Fill system with approved biodegradable hydraulic fluid.**

**The hydraulic system is now optimized for fluid biodegradability in the event of leakage.**



*"Solutions for a Greener World"*