



VST-9000-MHI

Articulated Telescopic Aerial Device

DEMAND BETTER.



- Max jib capacity: 1000 lbs



- Bucket capacity: 700 lbs
(with jib installed)/800 lbs
(without jib installed)



- Working height: 94'11"
- Horizontal reach: 56'8"



For more information about any of our outstanding VERSALIFT products, contact your authorized VERSALIFT Distributor or call 1.800.825.1085.



VST-9000-MHI

Articulated Telescopic Aerial Device

GENERAL SPECIFICATIONS

VST-9000-MHI

| | |
|------------------------------|--|
| Horizontal Reach Overcenter | 56'8" |
| Maximum Bucket Capacity | 700 lbs. (with jib installed)/800 lbs. (without jib installed) |
| Lower Boom Lift Eye Capacity | 1,500 lbs. (680kg) |
| Maximum Jib Capacity | 1,000 lbs. (454kg) |

HEIGHT WITH STANDARD REVERSE MOUNT PEDESTAL

| | |
|------------------------------|--------|
| Height to Bottom of Platform | 89'11" |
| Working Height | 94'11" |
| Stowed Travel Height | 12'5" |

HYDRAULIC SYSTEM

| | |
|--------------------|------------------------------------|
| Operating Pressure | 3000 psi (205 bars) |
| Flow Rate | 10 gpm (38 lpm) |
| Filtration | 10 Micron Return; 100 mesh Suction |
| System Type | Open Center |
| Power Source | PTO Pump |

BOOM ACTION

| | |
|-------------------------|-----------------|
| Upper Boom Articulation | -25° to +75° |
| Lower Boom Articulation | 0° to +88° |
| Inner boom extension | 198" |
| Rotation | 360° Continuous |
| Platform Rotation | 180° |

INSULATION GAPS

| | |
|---------------------------|-------------|
| Upper Boom Insulation Gap | 108" (2.7m) |
| Lower Boom Insulation Gap | 24" (.61m) |

VEHICLE REQUIREMENTS

| | |
|-----------------------|---------------|
| Cab to Axle (minimum) | 161.5" (4.1m) |
|-----------------------|---------------|

NOTE:

1. Specifications may vary without prior notification.
2. Required GVWR can vary significantly with chassis, lift mounting location, service body, accessories, and desired payload.



P.O. Box 20368
Waco, TX 76702-0368
254.399.2100
Fax: 254.399.2651
1.800.825.1085
www.timemfg.com